



Printing date 03/08/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

1 Identification

- **Product identifier:**
- **Trade name:** TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)
- **Product code:** TB-0786
- **Supplier Details**
- **Supplier:**
TOTALBOAT LLC
17 Peckham Drive
Bristol, RI 02809
Phone: 1-800-497-0010
Fax: 1-401-254-5829
- **Emergency telephone number:** INFOTRAC: 1-800-535-5053 (or go to www.infotrac.net)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Stoddard solvent

2-methoxy-1-methylethyl acetate

Xylene

- **Hazard statements**

Flammable liquid and vapor.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 2)



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/08/2016

Reviewed on 03/08/2016

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 1)

Do not breathe dust/fume/gas/mist/vapors/spray.
 Wear protective gloves / eye protection / face protection.
 Ground/bond container and receiving equipment.
 Keep container tightly closed.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 Do NOT induce vomiting.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store locked up.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 2
 Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *2
 Fire = 2
 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

8052-41-3	Stoddard solvent	25-50%
13463-67-7	titanium dioxide	2.5-<10%
1332-58-7	Kaolin	0.1-≤2.5%
64742-48-9	Hydrogen treated naphtha (Mineral spirits)	0.1-≤2.5%
1330-20-7	Xylene	0.1-≤2.5%
100-41-4	ethylbenzene	0.1-≤2.5%
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic	0.1-≤2.5%
108-65-6	2-methoxy-1-methylethyl acetate	0.1-≤2.5%

US

(Contd. on page 3)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 - Immediately remove any clothing soiled by the product.
 - Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
 - Rinse opened eye for several minutes under running water. If irritation occurs, get medical assistance.
- **After swallowing:** If symptoms persist consult doctor. Do not induce vomiting.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
 - No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
 - During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Mount respiratory protective device.
 - Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Keep respiratory protective device available.

(Contd. on page 4)



Printing date 03/08/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm

1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m ³ E; as respirable fraction

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

· Ingredients with biological limit values:

1330-20-7 Xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· Breathing equipment:

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

US

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 4)

Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:


Tightly sealed goggles

9 Physical and chemical properties
Information on basic physical and chemical properties
General Information
Appearance:

Form:	Liquid
Color:	Blue
Odor:	Characteristic
Odor threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	220 °C (428 °F)

Flash point: 40 °C (104 °F)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 230 °C (446 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Explosion limits:

Lower:	1.1 Vol %
Upper:	6.0 Vol %

Vapor pressure at 20 °C (68 °F): 2 hPa (2 mm Hg)

Density at 20 °C (68 °F): 1.009 g/cm³ (8.42 lbs/gal)

Relative density Not determined.

Vapor density Heavier than (Air)

(Contd. on page 6)



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/08/2016

Reviewed on 03/08/2016

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 5)

· Evaporation rate	Slower than (n-Butyl Acetate)
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· Solvent content:	
· VOC content:	370.0 g/l / 3.09 lb/gl
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	Xylene	3
100-41-4	ethylbenzene	2B
136-52-7	cobalt bis(2-ethylhexanoate)	2B
67-63-0	propan-2-ol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

US

(Contd. on page 7)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 6)



12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT, IATA | Paint |
| · IMDG | PAINT |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, IMDG, IATA | III |

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/08/2016

Reviewed on 03/08/2016

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 7)

· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	Flash Point – 100F or higher. D.O.T. label NOT required. 173.150(f)1 May be reclassified as Combustible Liquid.
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

100-41-4	ethylbenzene
95-63-6	1,2,4-Trimethylbenzene
136-52-7	cobalt bis(2-ethylhexanoate)
67-63-0	propan-2-ol

· TSCA (Toxic Substances Control Act):

8052-41-3	Stoddard solvent
13463-67-7	titanium dioxide
1332-58-7	Kaolin
64742-48-9	Hydrogen treated naphtha (Mineral spirits)
22464-99-9	Zirconium Carboxylate
100-41-4	ethylbenzene
108-65-6	2-methoxy-1-methylethyl acetate
68390-98-7	Quaternary ammonium compounds, benzyl-C14-18-alkyldimethyl, chlorides
95-63-6	1,2,4-Trimethylbenzene
136-52-7	cobalt bis(2-ethylhexanoate)
108-67-8	1,3,5-trimethylbenzene (mesitylene)
67-63-0	propan-2-ol

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7	titanium dioxide
------------	------------------

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 03/08/2016

Reviewed on 03/08/2016

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 8)

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	Xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
1332-58-7	Kaolin	A4
1330-20-7	Xylene	A4
100-41-4	ethylbenzene	A3
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Stoddard solvent

2-methoxy-1-methylethyl acetate

Xylene

· **Hazard statements**

Flammable liquid and vapor.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

(Contd. on page 10)



Printing date 03/08/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (QT)

(Contd. of page 9)

- IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 Do NOT induce vomiting.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store locked up.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **National regulations:**
 - **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group III (dangerous).
 - **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
 - **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** 03/08/2016 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 3: Flammable liquids, Hazard Category 3
 Muta. 1B: Germ cell mutagenicity, Hazard Category 1B
 Carc. 1B: Carcinogenicity, Hazard Category 1B
 Repr. 1B: Reproductive toxicity, Hazard Category 1B
 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1