

1 Identification

- **Product identifier:**
- **Trade name:** TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)
- **Product code:** TB-0122
- **Supplier Details**
- **Supplier:**
TOTALBOAT LLC
17 Peckham Drive
Bristol, RI 02809
Phone: 1-800-497-0010
Fax: 1-401-254-5829
- Emergency telephone number: INFOTRAC: 1-800-535-5053 (or go to www.infotrac.net)

2 Hazard(s) identification

- **Classification of the substance or mixture**



Flam. Liq. 3 H226 Flammable liquid and vapor.



Muta. 1B H340 May cause genetic defects.
Carc. 1A H350 May cause cancer.
Repr. 1B H360 May damage fertility or the unborn child.
STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



- **Signal word** Danger

- **Hazard-determining components of labeling:**

Stoddard solvent
2-methoxy-1-methylethyl acetate
Xylene
ethanol
2-butanone oxime

- **Hazard statements**

Flammable liquid and vapor.
May cause an allergic skin reaction.

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 1)

- May cause genetic defects.
- May cause cancer.
- May damage fertility or the unborn child.
- Causes damage to the central nervous system through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.

· **Precautionary statements**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing must not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If swallowed: Immediately call a poison center/doctor.
- Specific treatment (see on this label).
- Do NOT induce vomiting.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF exposed or concerned: Get medical advice/attention.
- Get medical advice/attention if you feel unwell.
- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- In case of fire: Use for extinction: CO2, powder or water spray.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

8052-41-3	Stoddard solvent	25-50%
13463-67-7	titanium dioxide	2.5-10%
1332-58-7	Kaolin	≤2.5%

(Contd. on page 3)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

		(Contd. of page 2)
1330-20-7	Xylene	≥0.1-≤2.5%
64-17-5	ethanol	≥0.1-≤2.5%
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic	≥0.1-≤2.5%
96-29-7	2-butanone oxime	≥0.1-<1%
100-41-4	ethylbenzene	≥0.1-≤2.5%
108-65-6	2-methoxy-1-methylethyl acetate	≥0.1-≤2.5%
136-52-7	cobalt bis(2-ethylhexanoate)	≥0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If irritation occurs, get medical assistance.
- **After swallowing:** If symptoms persist consult doctor. Do not induce vomiting.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:

8052-41-3	Stoddard solvent	300 mg/m ³
13463-67-7	titanium dioxide	30 mg/m ³
1330-20-7	Xylene	130 ppm
64-17-5	ethanol	1,800 ppm
96-29-7	2-butanone oxime	30 ppm
100-41-4	ethylbenzene	33 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
95-63-6	1,2,4-Trimethylbenzene	140 ppm
64742-48-9	Hydrogen treated naphtha (Mineral spirits)	350 mg/m ³
111-76-2	2-butoxyethanol	60 ppm
108-67-8	1,3,5-trimethylbenzene (mesitylene)	140 ppm
109-60-4	propyl acetate	250 ppm
67-63-0	propan-2-ol	400 ppm
14808-60-7	Silica, Crystalline	0.075 mg/m ³
108-88-3	toluene	67 ppm

· PAC-2:

8052-41-3	Stoddard solvent	1,800 mg/m ³
13463-67-7	titanium dioxide	330 mg/m ³
1330-20-7	Xylene	920* ppm
64-17-5	ethanol	3300* ppm
96-29-7	2-butanone oxime	56 ppm
100-41-4	ethylbenzene	1100* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
95-63-6	1,2,4-Trimethylbenzene	360 ppm
64742-48-9	Hydrogen treated naphtha (Mineral spirits)	1,800 mg/m ³
111-76-2	2-butoxyethanol	120 ppm
108-67-8	1,3,5-trimethylbenzene (mesitylene)	360 ppm
109-60-4	propyl acetate	1,300 ppm
67-63-0	propan-2-ol	2000* ppm
14808-60-7	Silica, Crystalline	33 mg/m ³
108-88-3	toluene	560 ppm

· PAC-3:

8052-41-3	Stoddard solvent	29500** mg/m ³
13463-67-7	titanium dioxide	2,000 mg/m ³
1330-20-7	Xylene	2500* ppm
64-17-5	ethanol	15000* ppm
96-29-7	2-butanone oxime	250 ppm
100-41-4	ethylbenzene	1800* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
95-63-6	1,2,4-Trimethylbenzene	480 ppm
64742-48-9	Hydrogen treated naphtha (Mineral spirits)	40,000 mg/m ³
111-76-2	2-butoxyethanol	700 ppm
108-67-8	1,3,5-trimethylbenzene (mesitylene)	480 ppm
109-60-4	propyl acetate	8000* ppm

(Contd. on page 5)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 4)

67-63-0	propan-2-ol	12000** ppm
14808-60-7	Silica, Crystalline	200 mg/m ³
108-88-3	toluene	3700* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm

1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m ³ E; as respirable fraction

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

(Contd. on page 6)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 5)

64-17-5 ethanol

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm

96-29-7 2-butanone oxime

WEEL	Long-term value: 10 ppm DSEN
------	---------------------------------

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

136-52-7 cobalt bis(2-ethylhexanoate)

TLV	Long-term value: (0.02) NIC-0.02* mg/m ³ as Co, *inhalable; NIC-DSEN; RSEN; BEI
-----	---

· Ingredients with biological limit values:

1330-20-7 Xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 7)

Trade name: TB WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 6)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Liquid

· **Color:** Blue

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/Melting range:** Undetermined.

· **Boiling point/Boiling range:** 149-213 °C (300.2-415.4 °F)

· **Flash point:** 40 °C (104 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 230 °C (446 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· **Lower:** 1.1 Vol %

· **Upper:** 6 Vol %

· **Vapor pressure at 20 °C (68 °F):** 2 hPa (1.5 mm Hg)

· **Density at 20 °C (68 °F):** 1.006 g/cm³ (8.39507 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Heavier than (Air)

· **Evaporation rate** Slower than (n-Butyl Acetate)

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 8)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 7)

- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
- **VOC content:** 370.0 g/l / 3.09 lb/gal
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent Naphtha (Petroleum), Light Aromatic

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	Xylene	3
64-17-5	ethanol	1
100-41-4	ethylbenzene	2B
136-52-7	cobalt bis(2-ethylhexanoate)	2B
111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
14808-60-7	Silica, Crystalline	1
108-88-3	toluene	3

· **NTP (National Toxicology Program)**

14808-60-7	Silica, Crystalline	K
------------	---------------------	---

(Contd. on page 9)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 8)

· **OSHA-Ca (Occupational Safety & Health Administration)**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.



12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · IMDG, IATA | PAINT |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| <hr style="border-top: 1px dashed black;"/> | |
| · IMDG, IATA | |
| |  |
| · Class | 3 Flammable liquids |

(Contd. on page 10)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 9)

· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	Flash Point – 100F or higher. D.O.T. label NOT required. 173.150(f)1 May be reclassified as Combustible Liquid.
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

8052-41-3	Stoddard solvent
1330-20-7	Xylene
64742-47-8	Naphtha Solvent
64-17-5	ethanol
96-29-7	2-butanone oxime
100-41-4	ethylbenzene
136-52-7	cobalt bis(2-ethylhexanoate)
95-63-6	1,2,4-Trimethylbenzene
111-76-2	2-butoxyethanol
109-60-4	propyl acetate
67-63-0	propan-2-ol
108-88-3	toluene

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

1330-20-7	Xylene
100-41-4	ethylbenzene

(Contd. on page 11)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 10)

136-52-7	cobalt bis(2-ethylhexanoate)
108-88-3	toluene

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
14808-60-7	Silica, Crystalline

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	Xylene	I
100-41-4	ethylbenzene	D
95-63-6	1,2,4-Trimethylbenzene	II
111-76-2	2-butoxyethanol	NL
108-67-8	1,3,5-trimethylbenzene (mesitylene)	II
108-88-3	toluene	II

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
1332-58-7	Kaolin	A4
1330-20-7	Xylene	A4
64-17-5	ethanol	A3
100-41-4	ethylbenzene	A3
111-76-2	2-butoxyethanol	A3
67-63-0	propan-2-ol	A4
14808-60-7	Silica, Crystalline	A2
108-88-3	toluene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
14808-60-7	Silica, Crystalline

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Stoddard solvent
2-methoxy-1-methylethyl acetate
Xylene
ethanol

(Contd. on page 12)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 11)

2-butanone oxime

· **Hazard statements**

- Flammable liquid and vapor.
- May cause an allergic skin reaction.
- May cause genetic defects.
- May cause cancer.
- May damage fertility or the unborn child.
- Causes damage to the central nervous system through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.

· **Precautionary statements**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Contaminated work clothing must not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If swallowed: Immediately call a poison center/doctor.
- Specific treatment (see on this label).
- Do NOT induce vomiting.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF exposed or concerned: Get medical advice/attention.
- Get medical advice/attention if you feel unwell.
- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- In case of fire: Use for extinction: CO₂, powder or water spray.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 06/20/2019 / 4

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 13)

Trade name: TOTALBOAT WET EDGE CLASSIC WHALER BLUE (GL)

(Contd. of page 12)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 1B: Germ cell mutagenicity – Category 1B
Carc. 1A: Carcinogenicity – Category 1A
Repr. 1B: Reproductive toxicity – Category 1B
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**