



Safety Data Sheet

1. Identification

Product Information. 4365429

Product Name: TotalBoat Underdog Blue

Recommended Use. Paints

Uses advised against. Read label instructions and SDS

Supplier. TOTALBOAT LLC
17 Peckham Drive
Bristol, Rhode Island 02809
1-800-497-0010

Emergency telephone number. Infotrac US & Canada: 1-800-535-5053
Infotrac International: 1-352-323-3500
24 hrs./day, 7 days/week

2. Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200

Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Carc. 1B, Eye Dam. 1, Flam. Liq. 3, Muta. 1B

GHS Pictograms



Signal Word

Danger

Unknown Acute Toxicity

14.3% of the mixture consists of ingredient(s) of unknown acute toxicity

HAZARD STATEMENTS

Flammable liquid and vapor.
Harmful if swallowed.
Causes serious eye damage.
Harmful if inhaled.
May cause genetic defects.
May cause cancer.

Precautionary Statements - Prevention.

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.

Take precautionary measures against static discharge.
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Wash face and hands and any exposed skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response.

If swallowed: Call a poison center/doctor if you feel unwell.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If exposed or concerned: Get medical advice/attention.
 Immediately call a poison center/doctor.
 Rinse mouth.
 In case of fire: Use CO₂ dry chemical or foam to extinguish.

Precautionary Statements - Storage.

Store in a well-ventilated place. Keep cool.
 Store locked up.

Precautionary Statements - Disposal.

Dispose of contents in accordance with local/regional/national/international regulations.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>
Cuprous oxide	1317-39-1	10-25
Petroleum distillates, light aromatic	64742-95-6	10-25
Barium Sulfate	7727-43-7	10-25
Zinc oxide	1314-13-2	2.5-10
1,2,4-TRIMETHYLBENZENE	95-63-6	2.5-10
Talc	14807-96-6	2.5-10
Titanium Dioxide	13463-67-7	2.5-10
MAGNESITE	546-93-0	2.5-10
Cupric Oxide	1317-38-0	0.1-1.0
XYLENE	1330-20-7	0.1-1.0
Copper (as Cu Dust & Mists)	7440-50-8	0.1-1.0
Benzene, (1-methylethyl)-	98-82-8	0.1-1.0
Ethyl Benzene	100-41-4	0.1-1.0

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid Measures

Description of first-aid measures.

General advice.

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice.
 Call a poison control center or doctor for treatment advice.

Inhalation.

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

Skin contact.

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

Eye contact.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

Ingestion.

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately.

Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

Notes to physician.

Treat symptomatically.

5. Fire-fighting Measures

Extinguishing media.**Suitable extinguishing media.**

Use: Dry powder. Alcohol-resistant foam. Carbon dioxide (CO₂). Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Extinguishing media which shall not be used for safety reasons.

Water may be unsuitable for extinguishing fires.

Special hazards arising from the substance or mixture.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Air/vapor mixtures may explode when ignited. Containers may explode when heated.

Advice for firefighters.

Evacuate personnel to safe areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures.**Personal precautions.**

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective gloves/clothing and eye/face protection. Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use.

Advice for emergency responders.

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

Environmental precautions.

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

Methods and materials for containment and cleaning up.**Methods for Containment.**

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment. Remove all sources of ignition.

Methods for cleaning up.

Prevent further leakage or spillage if safe to do so. Keep away from open flames, hot surfaces and sources of ignition. Keep in suitable and closed containers for disposal. All equipment used when handling the product must be grounded. Keep combustibles (wood, paper, oil, etc) away from spilled material. Ventilate the area. Use personal protective equipment as required. Shut off ignition sources; including electrical equipment and flames. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

Reference to other sections.

See section 8 for more information.

7. Handling and Storage**Conditions for safe storage, including any incompatibilities.****Advice on safe handling.**

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Use according to package label instructions. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Wash hands before breaks and immediately after handling the product. Ground and bond containers when transferring material. All equipment used when handling the product must be grounded.

Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Storage Conditions.

Keep container closed when not in use. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

8. Exposure Controls/Personal Protection**Ingredients with Occupational Exposure Limits**

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Barium Sulfate	5 mg/m ³	N.E.	15 mg/m ³	N.E.
Zinc oxide	2 mg/m ³	10 mg/m ³	5 mg/m ³	N.E.
Talc	2 mg/m ³	N.E.	N.E.	N.E.
Titanium Dioxide	10 mg/m ³	N.E.	15 mg/m ³	N.E.
XYLENE	100 ppm	150 ppm	100 ppm	N.E.
Copper (as Cu Dust & Mists)	0.2 mg/m ³	N.E.	0.1 mg/m ³	N.E.
Benzene, (1-methylethyl)-	50 ppm	N.E.	50 ppm	N.E.
Ethyl Benzene	20 ppm	N.E.	100 ppm	N.E.

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

Engineering Measures.

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment.

Eye/Face Protection.

If splashes are likely to occur, wear:. Face-shield. Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection.

Use:. Long sleeved clothing. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

Respiratory protection.

In case of inadequate ventilation wear respiratory protection. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

9. Physical and chemical properties.

Information on basic physical and chemical properties.

Physical state	Liquid
Appearance	No Information
Color	Blue
Odor	Aromatic solvent
Odor Threshold	No Information
pH	No Information
Melting/freezing point., °C (°F)	No Information
Flash Point., °C (°F)	25 (77.00)
Boiling point/boiling range., °C (°F)	138 - 3,600 (280.4 - 6512)
Evaporation rate	No Information Available
Explosive properties.	No Information
Vapor pressure.	No Information
Vapor density.	No Information
Specific Gravity. (g/cm ³)	1.880
Water solubility.	No Information
Partition coefficient.	No Information
Autoignition temperature., °C	No Information
Decomposition Temperature °C.	No Information
Viscosity, kinematic.	22 mm ² /s

Other information.

Volatile organic compounds (VOC) content.	No Information
Density, lb/gal	15.653

10. Stability and Reactivity

Reactivity.

Stable under normal conditions.

Chemical stability.

Stable under recommended storage conditions.

Possibility of hazardous reactions.

None known based on information supplied.

Conditions to Avoid.

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from heat and sources of ignition. Do not freeze.

Incompatible Materials.

None known based on information supplied.

Hazardous Decomposition Products.

Thermal decomposition can lead to release of irritating gases and vapours. Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

11. Toxicological Information**Information on toxicological effects.****Acute toxicity.****Product Information**

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	1,892.1 mg/kg
ATEmix (dermal)	4,004.3 mg/kg
ATEmix (inhalation - vapor)	30.23 mg/l

Component Information.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>LD50 Oral</u>	<u>LD50 Dermal</u>	<u>LC50 Inhalation</u>
1317-39-1	Cuprous oxide	470 mg/kg Rat	>2000 mg/kg Rat	N.I.
64742-95-6	Petroleum distillates, light aromatic	8400 mg/kg Rat	>2000 mg/kg Rabbit	3400 ppm Rat (Gas/Mist)
1314-13-2	Zinc oxide	>5000 mg/kg Rat	N.I.	N.I.
95-63-6	1,2,4-TRIMETHYLBENZENE	3280 mg/kg Rat	>3160 mg/kg Rabbit	18 mg/L Rat (Vapor)
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	N.I.	N.I.
1330-20-7	XYLENE	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat (Vapor)
98-82-8	Benzene, (1-methylethyl)-	1400 mg/kg Rat	1474 mg/kg Rabbit	>3577 ppm Rat (Gas/Mist)
100-41-4	Ethyl Benzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.4 mg/L Rat (Vapor)

N.I. = No Information

Skin corrosion/irritation.

SKIN IRRITANT.

Eye damage/irritation.

No Information

Respiratory or skin sensitization.

No Information

Ingestion.

May be harmful if swallowed.

Germ cell mutagenicity.

No Information

Carcinogenicity.

No Information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
14807-96-6	Talc	IARC Group 3	-	-

13463-67-7	Titanium Dioxide	IARC Group 2B	-	-
1330-20-7	XYLENE	IARC Group 3	-	-
98-82-8	Benzene, (1-methylethyl)-	IARC Group 2B	NTP Reasonably Anticipated to be Human Carcinogen	-
100-41-4	Ethyl Benzene	IARC Group 2B	-	-

Reproductive toxicity.

No Information

Specific target organ systemic toxicity (single exposure).

No Information

Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard.

No Information

Primary Route(s) of Entry

No Information

12. Ecological Information

Toxicity.

20.55% of the mixture consists of ingredient(s) of unknown aquatic toxicity

Ecotoxicity effects.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Cuprous oxide 1317-39-1	EC50 96 h Desmodesmus subspicatus 65 mg/L, EC50 96 h Pseudokirchneriella subcapitata 0.021 - 0.037 mg/L, EC50 96 h Pseudokirchneriella subcapitata 0.055 - 0.076 mg/L	-	EC50 48 h Daphnia magna 0.51 mg/L
Petroleum distillates, light aromatic 64742-95-6	-	LC50 96 h Oncorhynchus mykiss 9.22 mg/L	EC50 48 h Daphnia magna 6.14 mg/L
Zinc oxide 1314-13-2	-	LC50 96 h Danio rerio 1.55 mg/L	-
1,2,4-TRIMETHYLBENZENE 95-63-6	-	LC50 96 h Pimephales promelas 7.19 - 8.28 mg/L	EC50 48 h Daphnia magna 6.14 mg/L
Talc 14807-96-6	-	LC50 96 h Brachydanio rerio >100 g/L	-
XYLENE 1330-20-7	-	LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7.711 - 9.591 mg/L, LC50 96 h Pimephales promelas 23.53 - 29.97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40.	EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L

Copper (as Cu Dust & Mists) 7440-50-8	EC50 72 h Pseudokirchneriella subcapitata 0.0426 - 0.0535 mg/L, EC50 96 h Pseudokirchneriella subcapitata 0.031 - 0.054 mg/L	LC50 96 h Pimephales promelas 0.0068 - 0.0156 mg/L, LC50 96 h Pimephales promelas <0.3 mg/L, LC50 96 h Pimephales promelas 0.2 mg/L, LC50 96 h Oncorhynchus mykiss 0.052 mg/L, LC50 96 h Lepomis macrochirus 1.25 mg/L, LC50 96 h Cyprinus carpio 0.3 mg/L, LC50 96 h Cyprinus carpio 0.8 mg/L, LC50 96 h Poecilia reticulata 0.112 mg/L	EC50 48 h Daphnia magna 0.03 mg/L
Benzene, (1-methylethyl)- 98-82-8	EC50 72 h Pseudokirchneriella subcapitata 2.6 mg/L	LC50 96 h Pimephales promelas 6.04 - 6.61 mg/L, LC50 96 h Oncorhynchus mykiss 4.8 mg/L, LC50 96 h Oncorhynchus mykiss 2.7 mg/L, LC50 96 h Poecilia reticulata 5.1 mg/L	EC50 48 h Daphnia magna 0.6 mg/L, EC50 48 h Daphnia magna 7.9 - 14.1 mg/L
Ethyl Benzene 100-41-4	EC50 72 h Pseudokirchneriella subcapitata 4.6 mg/L, EC50 96 h Pseudokirchneriella subcapitata >438 mg/L, EC50 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L, EC50 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L	LC50 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L, LC50 96 h Oncorhynchus mykiss 4.2 mg/L, LC50 96 h Pimephales promelas 7.55 - 11 mg/L, LC50 96 h Lepomis macrochirus 32 mg/L, LC50 96 h Pimephales promelas 9.1 - 15.6 mg/L, LC50 96 h Poecilia reticulata 9.6 mg/L	EC50 48 h Daphnia magna 1.8 - 2.4 mg/L

Persistence and degradability.

No data are available on the product itself.

Bioaccumulative potential.

Discharge into the environment must be avoided.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>log POW</u>
95-63-6	1,2,4-TRIMETHYLBENZENE	3.63
1330-20-7	XYLENE	2.77 - 3.15
98-82-8	Benzene, (1-methylethyl)-	3.7
100-41-4	Ethyl Benzene	3.2

Mobility in soil.

No information

Other adverse effects.

No information

13. Disposal Considerations

Waste Disposal Guidance.

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes can not be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Shipping Name: Paint
Hazard Class: 3
UN/NA Number: 1263
Packing Group: III
Additional Information: DOT Ground - 'Non-bulk' shipments may be non-regulated per 49CFR 173.150(f)(2). Not regulated (If shipped In non-bulk packaging By ground transport).
 Limited Quantity: This product may be reclassified as Consumer Commodity, ORM-D, When shipped By ground; packaging quantity limitations apply(i.e.Quarts, Gallons).

IMDG

-

Proper Shipping Name: Paint
Hazard Class: 3
UN Number: 1263
Packing Group: III

IATA

Proper Shipping Name: UN1263, Paint
Hazard Class: 3
Packing Group: III

15. Regulatory Information

International Inventories:

TSCA	Complies
DSL	-
DSL/NDSL	-
EINECS/ELINCS	-
ENCS	-
IECSC	-
KECI	-
PICCS	-
AICS	-
NZIoC	-

TCSI

TSCA	United States Toxic Substances Control Act Section 8(b) Inventory.
DSL	Canadian Domestic Substances List.
DSL/NDSL	Canadian Domestic Substances List/Canadian Non-Domestic Substances List
EINECS/ELINCS	European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
ENCS	Japan Existing and New Chemical Substances.
IECSC	China Inventory of Existing Chemical Substances.
KECL	Korean Existing and Evaluated Chemical Substances.
PICCS	Philippines Inventory of Chemicals and Chemical Substances.
AICS	Australian Inventory of Chemical Substances.
NZIoC	New Zealand Inventory of Chemicals.
TCSI	Taiwan Chemical Substance Inventory

U.S. Federal Regulations:**SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Weight Percent</u>
1,2,4-TRIMETHYLBENZENE	95-63-6	2.5-10
Benzene, (1-methylethyl)-	98-82-8	0.1-1.0
Ethyl Benzene	100-41-4	0.1-1.0

TOXIC SUBSTANCES CONTROL ACT 12(b):

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:.

This product does not contain any chemicals that are subject to the reporting requirements of TSCA 12(b).

U.S. EPA PESTICIDE INFORMATION

EPA Pesticide Registration 60061-132

EPA STATEMENT: This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

EPA PESTICIDE LABEL: WARNING. Combustible liquid and vapor. Vapor harmful. Fatal if swallowed.
Causes eye irritation. Harmful if absorbed through the skin. May be fatal if swallowed or inhaled.

CALIFORNIA PROPOSITION 65 CARCINOGENS**WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:.

<u>Chemical Name</u>	<u>CAS-No.</u>
Titanium Dioxide	13463-67-7
Benzene, (1-methylethyl)-	98-82-8
Ethyl Benzene	100-41-4
Crystalline silica (Quartz) (Respirable)	14808-60-7
Lead	7439-92-1

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**WARNING**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
Lead	7439-92-1

16. Other Information

Revision Date: 1/10/2020 **Supersedes Date:** New SDS
Reason for revision: No Information
Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	2*	Flammability:	2	Physical Hazard:	0	Personal Protection:	X
----------------	----	----------------------	---	-------------------------	---	-----------------------------	---

NFPA Ratings:

Health:	2	Flammability:	2	Instability:	0	Physical & Chemical:	---
----------------	---	----------------------	---	---------------------	---	---------------------------------	-----

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.