

TOTALBOAT 5:1 FAST HARDENER

SECTION 1: IDENTIFICATION

GHS PRODUCT IDENTIFIERS:

PRODUCT NAME: TotalBoat 5:1 Fast Epoxy

Hardener

SYNONYMS, TRADE NAMES: TotalBoat 5:1 Fast Hardener, 5:1 Fast Hardener, Part A

OTHER MEANS OF IDENTIFICATION: Not Applicable

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE:

USES: Polymer Matrix For Fiber-Reinforced Plastic (FRP)

RESTRICTIONS ON USE: None Identified

SUPPLIER'S DETAILS:

SUPPLIER: TOTALBOAT LLC

17 Peckham Drive Bristol, RI 02809

TELEPHONE: +1 800 497 0010 FACSIMILE: +1 401 254 5829

EMERGENCY PHONE NUMBER:

INFOTRAC: 1 800 535 5053 (or go to www.infotrac.net)

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE:

Germ Cell Mutagenicity:

Acute toxicity, inhalation:

Acute toxicity, dermal:

Acute toxicity, oral:

Category 5, H333

Category 4, H312

Category 5, H303

Category 5, H303

Specific Target Organ Toxicity (RE):

Category 2, H373

Category 1, H314

Skin sensitization:

Category 1, H317

Hazardous to the aquatic environment: Acute Category 1, H400
Hazardous to the aquatic environment: Chronic Category 1, H410

GHS LABEL ELEMENTS:

HAZARD SYMBOLS:











TOTALBOAT 5:1 FAST HARDENER

SIGNAL WORDS: Danger

HAZARD STATEMENTS: H303 May be harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H333 May be harmful if inhaled.

H341 Suspected of causing genetic defects

H373 May cause damage to organs through prolonged or repeated

exposure.

H400 Very toxic to aquatic life.

H401 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

PREVENTION: P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breath mists.

P261 Avoid breathing dust, fumes, gas mist, vapors and spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, clothing, and eye/face protection.

RESPONSE: P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P314 Get medical attention if you feel unwell.

P303+P361+P364+P353+P352 IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water/shower. Wash

with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical attention.

P391 Collect spillage.

STORAGE: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

DISPOSAL: P501 Dispose of contents and containers in accordance with local, regional and

international regulations.

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS) – Annex III

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	CONTENT
Phenol	108-95-2	1-15%
Triethylenetetramine	112-24-3	<20%
Polyethylene Polyamines	68131-73-7	10-30%

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.



TOTALBOAT 5:1 FAST HARDENER

SECTION 4: FIRST-AID MEASURES

DESCRIPTION OF NECESSARY FIRST-AID MEASURES:

INHALATION: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing,

give artificial respiration.

SKIN: Immediately remove contaminated clothing and shoes. Wash the affected area with

plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. Get medical attention immediately.

EYES: Immediately flush eyes with plenty of clean water for an extended time, not less than

fifteen (15) minutes. Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and

roll eyes in a circular motion. Get medical attention immediately.

INGESTION: Do not induce vomiting. Never give anything by mouth to an unconscious person.

Rinse out the mouth with water. Get medical attention immediately.

MOST IMPORTANT SYMPTOMS AND EFFECTS, ACUTE AND DELAYED:

SYMPTOMS: Burns. Irritation. Pre-existing skin problems may be aggravated by prolonged or

repeated contact. Persons with sensitive airways (e.g., asthmatics) may react to

vapors. See section 11 for additional information.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED, IF

NECESSARY:

TREATMENT: Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA:

SUITABLE: Use water spray, foam, dry chemical or carbon dioxide.

UNSUITABLE: None known.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:

UNUSUAL FIRE & EXPLOSION HAZARDS: Product is not considered a fire hazard, but will burn if ignited. Closed container may rupture (due to build up in pressure) when exposed to extreme heat.

HAZARDOUS COMBUSTION PRODUCTS: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See Section 10 Hazardous decomposition products for additional information.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear self-contained breathing apparatus (SCBA) equipped with a full face piece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations. See section 9 for additional information.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: See Section 8 for recommendations on the use of personal protective equipment. If spilled in an enclosed area, ventilate. Eliminate ignition sources. Personal Protective Equipment must be worn.

ENVIRONMENTAL PRECAUTIONS: Do not flush product into public sewer, water systems or surface waters.



TOTALBOAT 5:1 FAST HARDENER

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Stop leak if without risk. Move containers from spill area. Contain by diking with sand, earth or other non-combustible material. Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Use under well-ventilated conditions. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Discard shoes contaminated with this product.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Keep away from heat, sparks and open flames. Store dry at 15-40°C, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use. Empty container contains residual product which may exhibit hazards of product. Do not reuse empty container without commercial cleaning or reconditioning.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS:

OCCUPATIONAL EXPOSURE LIMITS:

CHEMICAL NAME	CAS NUMBER	ACGIH-TWA	ACGIH-STEL
Phenol	108-95-2	2 ppm	Not available
Triethylenetetramine	112-24-3	Not available	Not available
Polyethylene Polyamines	68131-73-7	1 ppm	Not available

APPROPRIATE ENGINEERING CONTROLS: Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain air concentrations below occupational exposure standards. When necessary use mechanical handling to reduce human contact with materials.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT (PPE):

EYE/FACE Full face shield with safety glasses or goggles underneath are required.

PROTECTION:

SKIN Wear chemical resistant (impervious) gloves; PVC, neoprene, nitrile rubber, EVAL,

PROTECTION: butyl rubber. Wear chemical resistant protective clothing. Use good laboratory/

workplace procedures including personal protective clothing: lab coat and protective

RESPIRATORY

Wear an approved respirator (e.g., an organic vapor respirator, a full face air PROTECTION:

purifying respirator for organic vapors, or a self-contained breathing apparatus) whenever exposure to aerosol, mist, spray, fume or vapor exceed the applicable

exposure limit(s) of any chemical substance listed in this SDS.

GENERAL

Evewash fountains and safety showers are recommended in the work area.

PROTECTION:

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

UPPER/LOWER FLAMMABILTY OR APPEARANCE: Liquid Not available



TOTALBOAT 5:1 FAST HARDENER

EXPLOSIVE LIMITS:

(n-octanol/water):

COLOR: Clear amber VAPOUR PRESSURE: <1 mm Hg at 25°C ODOUR: Phenolic VAPOUR DENSITY: Heavier than air

ODOUR THRESHOLD:Not availableRELATIVE DENSITY:1.05PH:Not availableSOLUBILITY(IES):SlightlyMELTING POINT/Not availablePARTITION COEFFICIENTNot available

FREEZING POINT

INITIAL BOILING POINT Not avialable AUTO-IGNITION TEMPERATURE: Not available

AND BOILING RANGE:

FLASH POINT: >135°C **DECOMPOSITION TEMPERATURE:** Not available **EVAPORATION RATE:** Not available **VISCOSITY:** 1,060 cP at 25°C

FLAMMABILITY (SOLID, GAS):

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY: Exothermic reactions including polymerization may occur in contact with strong acids, strong bases, alcohols, strong oxidizing agents and excessive heat.

CHEMICAL STABILITY: This product is stable.

POSSIBILITY OF HAZARDOUS REACTIONS: Exothermic reactions including polymerization may occur in contact with strong acids, strong bases, alcohols, strong oxidizing agents and excessive heat.

CONDITIONS TO AVOID: Excessive heat and ignition sources.

Not available

INCOMPATIBLE MATERIALS: Avoid strong acids, bases, and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce smoke, carbon monoxide, carbon dioxide, aldehydes, oxides of nitrogen and other products of incomplete combustion.

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON THE LIKELY ROUTES OF EXPOSURE: Eyes, skin, inhalation and ingestion.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMCIAL AND TOXICOLOGICAL CHARACTERISTICS:

EYES: Causes severe eye damage.

SKIN: Harmful in contact with skin. Causes severe skin burns. May cause allergic skin

reaction.

INHALATION: May be harmful if inhaled. Exposure to vapors or mists may cause severe irritation and

burns of the nose, throat and respiratory tract.

INGESTION: May be harmful if swallowed. Ingestion may cause severe irritation and burns of the

mouth, throat and digestive tract.

DELAYED AND IMMEDIATE EFFECTS AND ALSO CHRONIC EFFECTS FROM SHORT AND LONG TERM EXPOSURE: Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure.

ACUTE TOXICITY:

CHEMICAL NAME LC_{50} INHALATION
(RAT) LD_{50} ORAL (RAT) LD_{50} DERMAL
(RABBIT)Phenol0.9 mg/L650 mg/kg630 mg/kgTriethylenetetramineNot available2,500 mg/kg805 mg/kg



TOTALBOAT 5:1 FAST HARDENER

Polyethylene Polyamines Not available 1,716 mg/kg >1,000 mg/kg

CORROSION / IRRITATION / SENSITIZATION INFORMATION:

SKIN CORROSION/IRRITATION: Skin Corrosion – Category 1B
SERIOUS EYE DAMAGE/IRRITATION: Information is not available.

RESPIRATORY OR SKIN SENSITIZATION: Skin Sensitization – Category 1

CARCINOGENICITY / MUTAGENICITY / REPRODUCTIVE TOXICOLOGY INFORMATION:

GERM CELL MUTAGENICITY: Germ Cell Mutagenicity – Category 2

CARCINOGENICITY: Information is not available. **REPRODUCTIVE TOXICITY:** Information is not available.

SPECIFIC TARGET ORGAN TOXICITY (STOT):

STOT-SINGLE EXPOSURE: Information is not available.

STOT-REPEATED EXPOSRE: STOT - Category 2

ASPIRATION HAZARD: Information is not available.

OTHER INFORMATION: Additional information is not available.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY:

CHEMICAL NAME TEST SPECIES RESULT 4-7 mg/L Phenol EC50 (48hrs) Daphnia Triethylenetetramine Not available Polyethylene Polyamines LC50 (96 hrs) **Fathead Minnow** 100 mg/L EC50 (48 hrs) Daphina 2.2 mg/L

ErC50 (48 hrs) Daphina 2.2 mg/L ErC50 (72 hrs) Green Algae 0.5 mg/L

PERSISTENCE AND DEGRADABILITY:

CHEMICAL NAME TEST PERIOD RESULT

Phenol Not available Triethylenetetramine Not available

Polyethylene Polyamines OECD 301B Test 28 days 9.5%

BIOACCUMULATIVE POTENTIAL:

CHEMICAL NAME Log Pow BCF POTENTIAL

Phenol Not available Not available Low

Triethylenetetramine Not available Not available Not available Not available

Polyethylene Polyamines -3.67 (estimated) <100 Low

MOBILITY IN SOIL:

CHEMICAL NAME SOIL/WATER PARTITION COEFFICIENT (Koc)

Phenol Not available
Triethylenetetramine Not available
Polyethylene Polyamines Not available

OTHER ADVERSE EFFECTS: Additional information is not available



TOTALBOAT 5:1 FAST HARDENER

SECTION 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of unused contents (incineration) in accordance with national and local regulations. Dispose of container in accordance with national and local regulations. Ensure the use of properly authorized waste management companies, where appropriate. See section 8 for recommendations on the use of personal protective equipment.

SECTION 14. TRANSPORTATION INFORMATION

UN NUMBER: UN2735

UN PROPER SHIPPING NAME: Polyamines, Liquid, Corrosive, N.O.S. (Polyethylenepolyamines)

TRANSPORT HAZARD CLASS:

U.S. DOT HAZARD CLASS: 8
CANADA TDG HAZARD CLASS: 8
EUROPE ADR/RID HAZARD CLASS: 8
IMDG CODE (OCEAN) HAZARD CLASS: 8
ICAO/IATA (AIR) HAZARD CLASS: 8

PACKING GROUP: III

ENVIRONMENTAL HAZARDS:

MARINE POLLUTANT: Yes HAZARDOUS SUBSTANCE (USA): Yes

SPECIAL PRECAUTIONS FOR USER: Information is not available.

TRANSPORTING IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:

Information is not available.

LABEL FOR CONVEYANCE:



OTHER INFORMATION: ORM-D Consumer Commodity in 1 gal or less containers

SECTION 15. REGULATORY INFORMATION

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT IN QUESTION:

EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV – List of substances subject to authorization, Substances of very high concern

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

None of the components are listed.

None of the

components are listed.

OTHER REGULATIONS: Additional information is not available.

CHEMICAL INVENTORIES:

Canadian Domestic Substances List (DSL):

Υ

Canadian Non-Domestic Substances List (NDSL):

Ν



SAFETY DATA SHEET TOTALBOAT 5:1 FAST HARDENER

European Inventory of Existing Chemical Substances (EINECS):

Y
European List of Notified Chemical Substances (ENCS):

N
U.S. Toxic Substances Control Act (TSCA):

Y

A "Y" listing indicates all intentionally added components are either listed or are otherwise compliant with the regulation. A "N" listing indicates that for one or more components: 1) there is no listing on the public inventory; 2) no information is available; or 3) the component has not been reviewed.

SECTION 16. OTHER INFORMATION

REVISION DATE: January 6, 2015

LEGEND: ACGIH: American Conference of Governmental Industrial Hygienists

ADR/RID: European dangerous goods transport road and rail regulations

CAS No: Chemical Abstract Service Registry Number

DOT: Department of Transportation (U.S.)

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods code

OEL: Occupational Exposure Limits

OSHA: Occupational Safety and Health Administration (U.S.)

PEL: Permissible Exposure Limit

RQ: Reportable Quantity SDS: Safety Data Sheet

STEL: Short Term Exposure Limit (15 minute Time Weighted Average) TDG: Canadian Transportation of Dangerous Goods Act and Regulations

UN: United Nations U.S.: United States

USERS RESPONSIBILITY/DISCLAIMER OF LIABILITY:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local laws and local regulations remains the responsibility of the user.