



Printing date 09/20/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 09/20/2016

1 Identification

- **Product identifier:**
- **Trade name:** TOTALBOAT MCTP G'WQQF'FPKU CLEAR SATIN (QT)
- **Product code:** TB-MWFS
- **Manufacturer details:**
- **Supplier:**
TOTALBOAT LLC
17 Peckham Drive
Bristol, RI 02809
Phone: 1-800-497-0010
Fax: 1-401-254-5829
- **Emergency telephone number:** INFOTRAC: 1-800-535-5053 (or go to www.infotrac.net)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 1 H360 May damage fertility or the unborn child.

STOT RE 1 H372-H373 Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Stoddard solvent

Xylene

Solvent Naphtha (Petroleum), Light Aromatic

ethylbenzene

(Contd. on page 2)



Printing date 09/20/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP G'WQQF 'FPHJ CLEAR SATIN (QT)

(Contd. of page 1)

Hazard statements

- Flammable liquid and vapor.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause genetic defects.
- May cause cancer.
- May damage fertility or the unborn child.
- Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.

Precautionary statements

- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wear protective gloves / eye protection / face protection.
- Ground/bond container and receiving equipment.
- Keep container tightly closed.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If skin irritation occurs: Get medical advice/attention.
- IF exposed or concerned: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Get medical advice/attention if you feel unwell.
- Do NOT induce vomiting.
- In case of fire: Use for extinction: CO2, powder or water spray.
- Take off contaminated clothing and wash it before reuse.
- Store locked up.
- Store in a well-ventilated place. Keep cool.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *2
Fire = 3
Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

- PBT:** Not applicable.
- vPvB:** Not applicable.

US

(Contd. on page 3)



Printing date 09/20/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP G'WQQF 'FPHJ CLEAR SATIN (QT)

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

8052-41-3	Stoddard solvent	10-<25%
98-56-6	Chlorobenzotrifluoride	2.5-<10%
1330-20-7	Xylene	2.5-<10%
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic	2.5-<10%
100-41-4	ethylbenzene	0.1-≤2.5%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	0.1-≤2.5%
872-50-4	N-methyl-2-pyrrolidone	0.1-≤2.5%
136-52-7	cobalt bis(2-ethylhexanoate)	0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor. Do not induce vomiting.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/20/2016

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP G'WQQF 'FPHJ CLEAR SATIN (QT)

(Contd. of page 3)

Reference to other sections

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.

Information about protection against explosions and fires:

- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

- Requirements to be met by storerooms and receptacles:** No special requirements.
- Information about storage in one common storage facility:** Not required.
- Further information about storage conditions:** Keep receptacle tightly sealed.
- Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems:** No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
- At this time, the other constituents have no known exposure limits.

8052-41-3 Stoddard solvent

PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm

1330-20-7 Xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

(Contd. on page 5)

Trade name: TOTALBOAT MCTIPG'WQQF'HPHJ CLEAR SATIN (QT)

(Contd. of page 4)

872-50-4 N-methyl-2-pyrrolidone

 WEEL Long-term value: 10 ppm
 Skin

136-52-7 cobalt bis(2-ethylhexanoate)

 TLV Long-term value: 0.02 mg/m³
 as Co, BEI

Ingredients with biological limit values:
1330-20-7 Xylene

 BEI 1.5 g/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Methylhippuric acids

100-41-4 ethylbenzene

 BEI 0.7 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
 -
 Medium: end-exhaled air
 Time: not critical
 Parameter: Ethyl benzene (semi-quantitative)

872-50-4 N-methyl-2-pyrrolidone

 BEI 100 mg/L
 Medium: urine
 Time: end of shift
 Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

 · **Additional information:** The lists that were valid during the creation were used as basis.

 · **Exposure controls**

 · **Personal protective equipment:**

 · **General protective and hygienic measures:**

 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.

 · **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

 · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)



Printing date 09/20/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP'G'WQQF'F'P'KJ CLEAR SATIN (QT)

(Contd. of page 5)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Amber colored
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	138 °C (280 °F)

- **Flash point:** 27 °C (81 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 230 °C (446 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	1.1 Vol %
Upper:	6.0 Vol %

- **Vapor pressure at 20 °C (68 °F):** 2 hPa (2 mm Hg)

- **Density at 20 °C (68 °F):** 0.984 g/cm³ (8.211 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Heavier than (Air)

- **Evaporation rate** Slower than (n-Butyl Acetate)

- **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

- **Solvent content:**

- **VOC content:** 351.0 g/l / 2.93 lb/gl

- **Other information** No further relevant information available.

(Contd. on page 7)



Printing date 09/20/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP G'WQQF 'FPHJ CLEAR SATIN (QT)

(Contd. of page 6)

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent Naphtha (Petroleum), Light Aromatic

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

1330-20-7	Xylene	3
100-41-4	ethylbenzene	2B
136-52-7	cobalt bis(2-ethylhexanoate)	2B
111-76-2	2-butoxyethanol	3
98-82-8	cumene	2B

· NTP (National Toxicology Program)

98-82-8	cumene	R
---------	--------	---

· OSHA-Ca (Occupational Safety & Health Administration)

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/20/2016

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP G'WQQF 'FPHJ CLEAR SATIN (QT)

(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263

- **UN proper shipping name**
- **DOT** Paint
- **IMDG, IATA** PAINT

- **Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

- **Packing group**
- **DOT, IMDG, IATA** III

- **Environmental hazards:** Not applicable.

- **Special precautions for user** Warning: Flammable liquids
- **Danger code (Kemler):** 30
- **EMS Number:** F-E, S-E
- **Stowage Category** A

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 9)

US



Printing date 09/20/2016

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP G'WQQF'FPHJ CLEAR SATIN (QT)

(Contd. of page 8)

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· Remarks:

Flash Point – 100F or higher. D.O.T. label NOT required.
173.150(f)1 May be reclassified as Combustible Liquid.

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 Xylene

100-41-4 ethylbenzene

872-50-4 N-methyl-2-pyrrolidone

136-52-7 cobalt bis(2-ethylhexanoate)

111-76-2 2-butoxyethanol

98-82-8 cumene

95-63-6 1,2,4-Trimethylbenzene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

98-82-8 cumene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

872-50-4 N-methyl-2-pyrrolidone

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 Xylene

I

100-41-4 ethylbenzene

D

111-76-2 2-butoxyethanol

NL

98-82-8 cumene

D, CBD

(Contd. on page 10)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/20/2016

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTIPGY QQF'HPKU CLEAR SATIN (QT)

(Contd. of page 9)

· TLV (Threshold Limit Value established by ACGIH)		
1330-20-7	Xylene	A4
100-41-4	ethylbenzene	A3
111-76-2	2-butoxyethanol	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Stoddard solvent

Xylene

Solvent Naphtha (Petroleum), Light Aromatic

ethylbenzene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the central nervous system and the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Keep container tightly closed.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO₂, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

(Contd. on page 11)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/20/2016

Reviewed on 09/20/2016

Trade name: TOTALBOAT MCTP'G'WQQF'F'P'KJ CLEAR SATIN (QT)

(Contd. of page 10)

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Dec'g'qhl't gr ct c'kqp'T'ic u't g'x'k'qp2; 424238'T5**

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

Repr. 1: Reproductive toxicity – Category 1

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

- *** Data compared to the previous version altered.**