

## 1 Identification

- **Product identifier:**
- **Trade name:** TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)  
TB-PRIMEGQ TOTALBOAT TOPSIDE PRIMER GRAY (QT)
- **Product code:** TB-PRIMEG
- **Supplier Details**
- **Supplier:**  
VQVCNDQC V'NNE  
39'Rgenj co 'F tkxg  
Dtkvqn TK02: 2;  
Rj qpg-3/: 22/6; 9/2232  
Hcz-3/623/476/7: 4;
- **Emergency telephone number:** 1-800-451-7777

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Xylene

Proprietary - Pentaerythritol Ester of Modified Rosin

2-methoxy-1-methylethyl acetate

Quartz (SiO<sub>2</sub>)

(Contd. on page 2)



Printing date 03/08/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEQG TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 1)

· **Hazard statements**

Highly flammable liquid and vapor.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause an allergic skin reaction.  
 May cause cancer.  
 May damage fertility or the unborn child.  
 May cause respiratory irritation.  
 May cause damage to the hearing organs through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves / eye protection / face protection.  
 Ground/bond container and receiving equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Specific treatment (see on this label).  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER/doctor if you feel unwell.  
 Wash contaminated clothing before reuse.  
 IF exposed or concerned: Get medical advice/attention.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Get medical advice/attention if you feel unwell.  
 Do NOT induce vomiting.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Take off contaminated clothing and wash it before reuse.  
 Store locked up.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2  
 Fire = 3  
 Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*2  
 Fire = 3  
 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)



Printing date 03/08/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEQG TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

· **vPvB:** Not applicable.

(Contd. of page 2)

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

1330-20-7	Xylene	10-<25%
67-64-1	acetone	10-<25%
14808-60-7	Quartz (SiO <sub>2</sub> )	2.5-<10%
	Proprietary - Pentaerythritol Ester of Modified Rosin	2.5-<10%
13463-67-7	titanium dioxide	2.5-<10%
100-41-4	ethylbenzene	2.5-<10%
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic	2.5-<10%
108-65-6	2-methoxy-1-methylethyl acetate	0.1-≤2.5%
872-50-4	N-methyl-2-pyrrolidone	0.1-≤2.5%

## 4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor. Do not induce vomiting.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

· **Extinguishing media**· **Suitable extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.· **For safety reasons unsuitable extinguishing agents:** Water with full jet· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**· **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

(Contd. on page 4)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/08/2016

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEGQ TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 3)

- Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.
- **Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Keep receptacle tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

### · Components with limit values that require monitoring at the workplace:

#### 1330-20-7 Xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

#### 67-64-1 acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm Long-term value: 594 mg/m <sup>3</sup> , 250 ppm BEI

(Contd. on page 5)



Printing date 03/08/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEQG TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 4)

**14808-60-7 Quartz (SiO<sub>2</sub>)**

PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**872-50-4 N-methyl-2-pyrrolidone**

WEEL	Long-term value: 10 ppm Skin
------	---------------------------------

**· Ingredients with biological limit values:****1330-20-7 Xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**67-64-1 acetone**

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

**872-50-4 N-methyl-2-pyrrolidone**

BEI	100 mg/L Medium: urine Time: end of shift Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Store protective clothing separately.

(Contd. on page 6)

US

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEGQ TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 5)

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	Grey
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· <b>pH-value:</b>	Not determined.
--------------------	-----------------

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	55 °C (131 °F)

· <b>Flash point:</b>	-19 °C (-2 °F)
-----------------------	----------------

· <b>Flammability (solid, gaseous):</b>	Not applicable.
---	-----------------

· <b>Ignition temperature:</b>	432 °C (810 °F)
--------------------------------	-----------------

· <b>Decomposition temperature:</b>	Not determined.
-------------------------------------	-----------------

· <b>Auto igniting:</b>	Product is not selfigniting.
-------------------------	------------------------------

· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
-------------------------------	--

· **Explosion limits:**

· <b>Lower:</b>	1.0 Vol %
· <b>Upper:</b>	13.0 Vol %

(Contd. on page 7)



Printing date 03/08/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEQG TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 6)

· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)
· Density at 20 °C (68 °F):	1.271 g/cm <sup>3</sup> (10.606 lbs/gal)
· Relative density	Not determined.
· Vapor density	Heavier than (Air)
· Evaporation rate	Slower than (n-Butyl Acetate)
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	343.0 g/l / 2.86 lb/gl
· Other information	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
14807-96-6	Talc (hydrous magnesium silicate)	2B
1330-20-7	Xylene	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
136-52-7	cobalt bis(2-ethylhexanoate)	2B
98-82-8	cumene	2B
67-63-0	propan-2-ol	3

(Contd. on page 8)

US



Printing date 03/08/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEQG TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 7)

· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
98-82-8	cumene	R
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.		


## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 1 (Self-assessment): slightly hazardous for water  
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· <b>UN-Number</b>	
· <b>DOT, IMDG, IATA</b>	UN1263
· <b>UN proper shipping name</b>	
· <b>DOT, IATA</b>	Paint
· <b>IMDG</b>	PAINT
· <b>Transport hazard class(es)</b>	
· <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids

(Contd. on page 9)





Printing date 03/08/2016


# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEGQ TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 8)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### · Section 313 (Specific toxic chemical listings):

100-41-4	ethylbenzene
872-50-4	N-methyl-2-pyrrolidone
136-52-7	cobalt bis(2-ethylhexanoate)
98-82-8	cumene
67-63-0	propan-2-ol

### · TSCA (Toxic Substances Control Act):

14807-96-6	Talc (hydrous magnesium silicate)
67-64-1	acetone
14808-60-7	Quartz (SiO <sub>2</sub> )
13463-67-7	titanium dioxide
100-41-4	ethylbenzene

(Contd. on page 10)



Printing date 03/08/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEGQ TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 9)

108-65-6	2-methoxy-1-methylethyl acetate
872-50-4	N-methyl-2-pyrrolidone
68390-98-7	Quaternary ammonium compounds, benzyl-C14-18-alkyldimethyl, chlorides
546-93-0	Magnesite
136-52-7	cobalt bis(2-ethylhexanoate)
22464-99-9	Zirconium Carboxylate
98-82-8	cumene
15956-58-8	Manganese Carboxylate
67-63-0	propan-2-ol
7447-41-8	lithium chloride

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO <sub>2</sub> )
13463-67-7	titanium dioxide
100-41-4	ethylbenzene
98-82-8	cumene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

872-50-4	N-methyl-2-pyrrolidone
----------	------------------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	Xylene	I
67-64-1	acetone	I
100-41-4	ethylbenzene	D
98-82-8	cumene	D, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc (hydrous magnesium silicate)	A4
1330-20-7	Xylene	A4
67-64-1	acetone	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
13463-67-7	titanium dioxide	A4
100-41-4	ethylbenzene	A3
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO <sub>2</sub> )
13463-67-7	titanium dioxide

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 11)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/08/2016

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEQG TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 10)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Xylene  
 Proprietary - Pentaerythritol Ester of Modified Rosin  
 2-methoxy-1-methylethyl acetate  
 Quartz (SiO<sub>2</sub>)

· **Hazard statements**

Highly flammable liquid and vapor.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause an allergic skin reaction.  
 May cause cancer.  
 May damage fertility or the unborn child.  
 May cause respiratory irritation.  
 May cause damage to the hearing organs through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves / eye protection / face protection.  
 Ground/bond container and receiving equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Specific treatment (see on this label).  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER/doctor if you feel unwell.  
 Wash contaminated clothing before reuse.  
 IF exposed or concerned: Get medical advice/attention.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Get medical advice/attention if you feel unwell.  
 Do NOT induce vomiting.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Take off contaminated clothing and wash it before reuse.  
 Store locked up.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/08/2016

Reviewed on 03/08/2016

**Trade name: TB-PRIMEGG TOTALBOAT TOPSIDE PRIMER GRAY (GL)**  
**TB-PRIMEQG TOTALBOAT TOPSIDE PRIMER GRAY (QT)**

(Contd. of page 11)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**  
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.  
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision 03/08/2016 / -**

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flam. Liq. 2: Flammable liquids, Hazard Category 2  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A  
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1  
 Carc. 1A: Carcinogenicity, Hazard Category 1A  
 Repr. 1B: Reproductive toxicity, Hazard Category 1B  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2  
 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

US