

## 1 Identification

- **Product identifier:**
- **Trade name:** TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)  
TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)
- **Product code:** TB-BILGEW
- **Manufacturer details**
- **Supplier:**  
VQVCNDQCVNNE  
39' Rgenj co 'F tkxg  
Dtkvqn TK02: 2;  
Rj qpg<3/: 22/6; 9/2232  
Hcz<3/623/476/7: 4;
- **Emergency telephone number:** 1-800-441-4411

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

titanium dioxide

Xylene

Solvent Naphtha (Petroleum), Light Aromatic

n-butyl acetate

- **Hazard statements**

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

(Contd. on page 2)



Printing date 03/04/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 1)

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

13463-67-7	titanium dioxide	10-<25%
123-86-4	n-butyl acetate	10-<25%
1330-20-7	Xylene	10-<25%
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic	2.5-<10%
100-41-4	ethylbenzene	2.5-<10%

(Contd. on page 3)



Printing date 03/04/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 2)

98-82-8	cumene	0.1-≤2.5%
136-52-7	cobalt bis(2-ethylhexanoate)	0.1-≤2.5%

## 4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If irritation occurs, get medical assistance.

- **After swallowing:** If symptoms persist consult doctor. Do not induce vomiting.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

US

(Contd. on page 4)



Printing date 03/04/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 3)

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

### · Components with limit values that require monitoring at the workplace:

#### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m <sup>3</sup> , (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m <sup>3</sup> , (150) NIC-50 ppm

#### 1330-20-7 Xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

#### 100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

### · Ingredients with biological limit values:

#### 1330-20-7 Xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

(Contd. on page 5)

US

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 4)

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	-
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid  
**Color:** White

(Contd. on page 6)

US



Printing date 03/04/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 5)

· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	124 °C (255 °F)
· <b>Flash point:</b>	27 °C (81 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	370 °C (698 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1.0 Vol %
<b>Upper:</b>	7.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	10.7 hPa (8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.173 g/cm <sup>3</sup> (9.789 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Heavier than (Air)
· <b>Evaporation rate</b>	Slower than (n-Butyl Acetate)
· <b>Solubility in / Miscibility with</b>	
<b>Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC content:</b>	440.0 g/l / 3.67 lb/gl
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.

(Contd. on page 7)

US



Printing date 03/04/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 6)

- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
 The product shows the following dangers according to internally approved calculation methods for preparations:  
 Harmful  
 Irritant
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	Xylene	3
100-41-4	ethylbenzene	2B
98-82-8	cumene	2B
136-52-7	cobalt bis(2-ethylhexanoate)	2B
67-63-0	propan-2-ol	3

· **NTP (National Toxicology Program)**

98-82-8	cumene	R
---------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
 Water hazard class 1 (Self-assessment): slightly hazardous for water  
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

US

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS



Printing date 03/04/2016

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 7)

## 14 Transport information

· UN-Number	UN1263
· DOT, IMDG, IATA	
· UN proper shipping name	Paint
· DOT, IATA	PAINT
· IMDG	
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

US





Printing date 03/04/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 8)

· **Section 313 (Specific toxic chemical listings):**

100-41-4	ethylbenzene
98-82-8	cumene
136-52-7	cobalt bis(2-ethylhexanoate)
67-63-0	propan-2-ol

· **TSCA (Toxic Substances Control Act):**

13463-67-7	titanium dioxide
123-86-4	n-butyl acetate
1317-65-3	Ground Limestone (Calcium Carbonate)
100-41-4	ethylbenzene
22464-99-9	Zirconium Carboxylate
98-82-8	cumene
136-52-7	cobalt bis(2-ethylhexanoate)
68390-98-7	Quaternary ammonium compounds, benzyl-C14-18-alkyldimethyl, chlorides
64742-48-9	Hydrogen treated naphtha (Mineral spirits)
67-63-0	propan-2-ol
7732-18-5	water, distilled, conductivity or of similar purity

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
100-41-4	ethylbenzene
98-82-8	cumene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.
------------------------------------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.
------------------------------------

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.
------------------------------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	Xylene	I
100-41-4	ethylbenzene	D
98-82-8	cumene	D, CBD

· **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
1330-20-7	Xylene	A4
100-41-4	ethylbenzene	A3
67-63-0	propan-2-ol	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)**  
**TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 9)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Warning· **Hazard-determining components of labeling:**

titanium dioxide  
 Xylene  
 Solvent Naphtha (Petroleum), Light Aromatic  
 n-butyl acetate

· **Hazard statements**

Flammable liquid and vapor.  
 Harmful if inhaled.  
 Causes skin irritation.  
 Suspected of causing cancer.  
 May cause drowsiness or dizziness.  
 May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves / eye protection / face protection.  
 Ground/bond container and receiving equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 Specific treatment (see on this label).  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a POISON CENTER/doctor if you feel unwell.  
 If skin irritation occurs: Get medical advice/attention.  
 IF exposed or concerned: Get medical advice/attention.  
 Get medical advice/attention if you feel unwell.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Take off contaminated clothing and wash it before reuse.  
 Store locked up.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision 03/04/2016 / 1**

(Contd. on page 11)



Printing date 03/04/2016

# Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/04/2016

**Trade name: TB-BILGEWG TOTALBOAT VQVCNBILGE PAINT WHITE (GL)  
TB-BILGEWQ TOTALBOAT VQVCNBILGE PAINT WHITE (QT)**

(Contd. of page 10)

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Flam. Liq. 3: Flammable liquids, Hazard Category 3  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
 Carc. 2: Carcinogenicity, Hazard Category 2  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

· **\* Data compared to the previous version altered.**

US