

TotalBoat TotalStrip Paint Remover - Tech Data Sheet

SUPPORT PRODUCTS:

Cleanup: Water

COMPATIBLE SUBSTRATES:

Wood: Yes

Stone: Yes

Metal: Yes

Fiberglass: Yes

APPLICATION:

- 1: Apply TotalBoat TotalStrip between 1/4 to 1/2 inch thick using a brush, putty knife, or roller.
- 2: Allow paint stripper to work through the layers of paint, with more layers requiring longer time.
- 3: Lift off finishes using a putty knife or stiff brush.
- 4: Remove remaining residue using a brush or stripping pad with water.
- 5: Make sure the surface is completely dry before priming or painting.

APPLICATION DATA:

Application Method: Brush, Putty Knife, or Roller

Number of Coats: 1

Components: One

Film Thickness (per Coat): 1-2 mils dry (3 mils wet)

Application Temperature: 60-80°F

Application Humidity: 0-90%

Coverage (per Gallon): 50-75 sq. ft.

PHYSICAL DATA:

Solids (by Weight): 12.22 %

Solids (by Volume): 8.76 %

Weight (per Gallon): 9.16 lbs.

VOC Weight (per Gallon): 8.04 lbs.

Water Weight (per Gallon): 0 lbs.

VOC (g/L): 990

Color: Beige

