

Reviewed on 06/09/2023

## **1 Identification**

- Product identifier:
- Trade name: TOTALBOAT ALUMINUM BOAT PAINT ARMY GREEN
- · Product code: TB-0628, TB-1784
- · Details of the supplier of the safety data sheet
- Distributor: TOTALBOAT LLC 17 Peckham Drive Bristol, RI 02809 (800) 497-0010
- Emergency telephone number: INFOTRAC: 800-535-5053

## 2 Hazard(s) identification

· Classification of the substance or mixture



Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling: N-methyl-2-pyrrolidone 2-(2-methoxyethoxy)ethanol · Hazard statements May damage fertility or the unborn child. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. IF exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. • **vPvB:** Not applicable.

(Contd. on page 2)

Printing date 06/09/2023

Reviewed on 06/09/2023

### Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN

(Contd. of page 1)

## **3** Composition/information on ingredients

#### · Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
13463-67-7	titanium dioxide	2.5-10%
872-50-4	N-methyl-2-pyrrolidone	≥0.1-≤2.5%
111-77-3	2-(2-methoxyethoxy)ethanol	≥0.1-≤2.5%

### **4 First-aid measures**

· Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If irritation occurs, get medical assistance.
- After swallowing: If symptoms persist consult doctor. Do not induce vomiting.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### **6** Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

• Environmental precautions:

- Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to section 13.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

	· PAC-1:		
	13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
ſ	872-50-4	N-methyl-2-pyrrolidone	30 ppm
ſ	7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
		(C	ontd. on page 3)

Printing date 06/09/2023

Reviewed on 06/09/2023

## Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN

	(	Contd. of page
21645-51-2	aluminium hydroxide	8.7 mg/m <sup>3</sup>
111-77-3	2-(2-methoxy)ethanol	3.4 ppm
121-44-8	triethylamine	1 ppm
57-55-6	Propylene glycol	30 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
546-93-0	Magnesite	45 mg/m <sup>3</sup>
108-01-0	2-dimethylaminoethanol	3.7 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm
9005-00-9	Polyoxyethylene stearyl ether	5.7 mg/m <sup>2</sup>
· PAC-2:		
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
872-50-4	N-methyl-2-pyrrolidone	32 ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
21645-51-2	aluminium hydroxide	73 mg/m <sup>3</sup>
111-77-3	2-(2-methoxyethoxy)ethanol	37 ppm
121-44-8	triethylamine	170 ppm
57-55-6	Propylene glycol	1,300 mg/m
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
546-93-0	Magnesite	260 mg/m <sup>3</sup>
108-01-0	2-dimethylaminoethanol	40 ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm
9005-00-9	Polyoxyethylene stearyl ether	63 mg/m <sup>3</sup>
· PAC-3:	· · · · ·	
13463-67-7	titanium dioxide	2,000 mg/m
872-50-4	N-methyl-2-pyrrolidone	190 ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
21645-51-2	aluminium hydroxide	440 mg/m <sup>3</sup>
111-77-3	2-(2-methoxyethoxy)ethanol	220 ppm
121-44-8	triethylamine	1,000 ppm
57-55-6	Propylene glycol	7,900 mg/m
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
546-93-0	Magnesite	1,600 mg/m
108-01-0	2-dimethylaminoethanol	72 ppm
556-67-2		130 ppm
9005-00-9	Polyoxyethylene stearyl ether	380 mg/m <sup>3</sup>

## 7 Handling and storage

· Handling:

- Precautions for safe handling Open and handle receptacle with care.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

US

Printing date 06/09/2023

Reviewed on 06/09/2023

### Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN

(Contd. of page 3)

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.
- · Instructions for use:

Stir well before using. Keep from freezing.

### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

#### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

### 872-50-4 N-methyl-2-pyrrolidone

### TLV BEI

WEEL Long-term value: 10 ppm Skin

#### · Ingredients with biological limit values:

### 872-50-4 N-methyl-2-pyrrolidone

### BEI 100 mg/L Medium: urine

Time: end of shift Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

• Additional information: The lists that were valid during the creation were used as basis.

### · Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- · Breathing equipment: Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 06/09/2023

Reviewed on 06/09/2023

## Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling.

## 9 Physical and chemical properties

· Information on basic physical and che	mical properties
· General Information	
· Appearance:	Liquid
Form: Color:	Liquid Green
· Odor:	Characteristic
· Odor:	Not determined.
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
<b>Boiling point/Boiling range:</b>	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
<sup>·</sup> Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.23 g/cm <sup>3</sup> (10.26435 lbs/gal)
· Relative density	Not determined.
· Vapor density	Heavier than (Air)
· Evaporation rate	Slower than (n-Butyl Acetate)
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/water)	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
· Solvent content:	
VOC content:	4.17 %
	51.3 g/l / 0.43 lb/gal
· Other information	No further relevant information available.

## **10 Stability and reactivity**

· Reactivity No further relevant information available.

(Contd. on page 6)

(Contd. of page 4)

<sup>—</sup> US

Printing date 06/09/2023

Reviewed on 06/09/2023

### **Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN**

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

mg/kg (rabbit)

### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:

## · LD/LC50 values that are relevant for classification:

### 13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabb

Inhalative LC50/4 h > 6.82 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

### · Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
14807-96-6	Talc (hydrous magnesium silicate)	3
13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
· NTP (Natio	nal Toxicology Program)	

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 7)

(Contd. of page 5)

Printing date 06/09/2023

Reviewed on 06/09/2023

(Contd. of page 6)

### Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN

• **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	Not applicable/Not regulated	
UN proper shipping name DOT, IMDG, IATA	Not applicable/Not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	Not applicable/Not regulated	
Packing group		
DOT, IMDG, IATA	Not applicable/Not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

### **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

872-50-4 N-methyl-2-pyrrolidone

111-77-3 2-(2-methoxyethoxy)ethanol

121-44-8 triethylamine

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 8)

US

Printing date 06/09/2023

Reviewed on 06/09/2023

### Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN

Hazardona	Air Pollutants (	Contd. of page
121-44-8 tri	•	
<ul> <li>Proposition</li> </ul>	65	
· Chemicals l	known to cause cancer:	
13463-67-7	titanium dioxide	
1333-86-4	Carbon black	
	known to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
· Chemicals l	known to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
· Chemicals l	known to cause developmental toxicity:	
872-50-4 N	-methyl-2-pyrrolidone	
· Carcinogen	ic categories	
· EPA (Envir	onmental Protection Agency)	
None of the	ingredients is listed.	
· TLV (Three	shold Limit Value)	
13463-67-7	titanium dioxide	A
121-44-8	triethylamine	A
1333-86-4	Carbon black	A
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide	
1333-86-4	Carbon black	

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labeling:
- N-methyl-2-pyrrolidone
- 2-(2-methoxyethoxy)ethanol
- · Hazard statements
- May damage fertility or the unborn child.
- · Precautionary statements
- Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

- IF exposed or concerned: Get medical advice/attention.
- Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

Printing date 06/09/2023

Reviewed on 06/09/2023

### Trade name: TOTALBOAT ALUMINUM BOAT PAINT - ARMY GREEN

(Contd. of page 8)

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 06/09/2023 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Toxic to Reproduction 1B: Reproductive toxicity - Category 1B