

Reviewed on 06/09/2023

1 Identification

· Product identifier:

· Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

· Product code: TB-0633, TB-1787

· Details of the supplier of the safety data sheet

· Distributor:

TOTALBOAT LLC 17 Peckham Drive Bristol, RI 02809 (800) 497-0010

· Emergency telephone number: INFOTRAC: 800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

N-methyl-2-pyrrolidone

Carbon black

2-(2-methoxyethoxy)ethanol

· Hazard statements

Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 2)

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

· vPvB: Not applicable.

(Contd. of page 1)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous	· Dangerous components:		
1333-86-4	Carbon black	2.5-10%	
13463-67-7	titanium dioxide	2.5-10%	
872-50-4	N-methyl-2-pyrrolidone	≥0.1-≤2.5%	
111-77-3	2-(2-methoxyethoxy)ethanol	≥0.1-≤2.5%	

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact:

Rinse opened eye for several minutes under running water. If irritation occurs, get medical assistance.

- · After swallowing: If symptoms persist consult doctor. Do not induce vomiting.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

· PAC-1:		
	Carbon black	9 mg/m³
13463-67-7	titanium dioxide	30 mg/m ³
	N-methyl-2-pyrrolidone	30 ppm
	2-(2-methoxyethoxy)ethanol	3.4 ppm
	triethylamine	1 ppm
	Propylene glycol	30 mg/m ²
	silicon dioxide, chemically prepared	18 mg/m ²
	aluminium hydroxide	8.7 mg/m
546-93-0	Magnesite	45 mg/m ²
	2-dimethylaminoethanol	3.7 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm
	Polyoxyethylene stearyl ether	5.7 mg/m
· PAC-2:		
1333-86-4	Carbon black	99 mg/m³
13463-67-7	titanium dioxide	330 mg/m³
872-50-4	N-methyl-2-pyrrolidone	32 ppm
111-77-3	2-(2-methoxyethoxy)ethanol	37 ppm
121-44-8	triethylamine	170 ppm
57-55-6	Propylene glycol	1,300 mg/m
7631-86-9	silicon dioxide, chemically prepared	740 mg/m³
21645-51-2	aluminium hydroxide	73 mg/m ³
546-93-0	Magnesite	260 mg/m ³
108-01-0	2-dimethylaminoethanol	40 ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm
9005-00-9	Polyoxyethylene stearyl ether	63 mg/m ³
· PAC-3:		
1333-86-4	Carbon black	590 mg/m ³
13463-67-7	titanium dioxide	2,000 mg/m
872-50-4	N-methyl-2-pyrrolidone	190 ppm
111-77-3	2-(2-methoxyethoxy)ethanol	220 ppm
	triethylamine	1,000 ppm
57-55-6	Propylene glycol	7,900 mg/m
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m
21645-51-2	aluminium hydroxide	440 mg/m³
	Magnesite	1,600 mg/m
108-01-0	2-dimethylaminoethanol	72 ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm
	Polyoxyethylene stearyl ether	380 mg/m³

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling Open and handle receptacle with care.
- Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.
- · Instructions for use:

Stir well before using. Keep from freezing.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

1333-8	6-4 Carbon black
PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m³ *inhalable fraction, A3
872-50	-4 N-methyl-2-pyrrolidone
TLV	BEI
WEEL	Long-term value: 10 ppm Skin
T., d	ioute with histograph limit values.

· Ingredients with biological limit values:

872-50-4 N-methyl-2-pyrrolidone

BEI 100 mg/L Medium: urine

Time: end of shift

Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment: Not required.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

Information on basic physical and c	hemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Black	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
Density at 20 °C (68 °F):	1.169 g/cm³ (9.75531 lbs/gal)	
Relative density	Not determined.	
Vapor density	Heavier than (Air)	
Evaporation rate	Slower than (n-Butyl Acetate)	
Solubility in / Miscibility with		
Water:	Fully miscible.	

(Contd. on page 6)

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

Partition coefficient (n-octanol/water): Not determined.
Dynamic: Not determined.
Kinematic: Not determined.

Solvent content:
VOC content: 4.83 %
56.5 g/l / 0.47 lb/gal

Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values that are	relevant for	classification:
-----------	-----------------	--------------	-----------------

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
14807-96-6	Talc (hydrous magnesium silicate)	3
1333-86-4	Carbon black	2B
13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- **Behavior in environmental systems:**
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

Transport information		
UN-Number DOT, IMDG, IATA	Not applicable/Not regulated	
UN proper shipping name DOT, IMDG, IATA	Not applicable/Not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA Class	Not applicable/Not regulated	
Packing group DOT, IMDG, IATA	Not applicable/Not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.	

(Contd. on page 8)

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

(Contd. of page 7)

· UN "Model Regulation": Not applicable/Not regulated

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355	(extremely	hazardous	substances'):
---------------	------------	-----------	-------------	----

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

872-50-4 N-methyl-2-pyrrolidone

111-77-3 2-(2-methoxyethoxy)ethanol

121-44-8 triethylamine

TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Hazardous Air Pollutants

121-44-8 triethylamine

· Proposition 65

· Chemicals known to cause cancer:

1333-86-4 Carbon black

13463-67-7 titanium dioxide

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

872-50-4 N-methyl-2-pyrrolidone

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

1333-86-4	Carbon black	A4
13463-67-7	titanium dioxide	A4
121-44-8	triethylamine	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 C	arbon black
-------------	-------------

13463-67-7 titanium dioxide

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Printing date 06/09/2023 Reviewed on 06/09/2023

Trade name: TOTALBOAT ALUMINUM BOAT PAINT - BLACK

· Hazard pictograms

(Contd. of page 8)



· Signal word Danger

· Hazard-determining components of labeling:

N-methyl-2-pyrrolidone

Carbon black

2-(2-methoxyethoxy)ethanol

· Hazard statements

Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Date of preparation / last revision 06/09/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Carcinogenicity 2: Carcinogenicity – Category 2

Toxic to Reproduction 1B: Reproductive toxicity - Category 1B