



TOTALBOAT PREMIUM BOAT WAX

- Easy to apply and remove
- Carnauba wax formula
- Protects and shines brighter
- Contains ultra-fine abrasives to improve color
- Safe for use on fiberglass, gelcoat, metals, painted surfaces, clear coats

TotalBoat Premium Boat Wax is a soft paste marine wax that provides long-lasting protection from UV radiation, dirt, salt, and oxidation. This easy-to-apply carnauba wax formula dries quickly, and is easy to remove.

CLEANUP: Mild soap and water

SUBSTRATES: Fiberglass, gelcoat, epoxy, metals, paint, clear coat, automotive paints

ASSOCIATED APPLICATION TOOLS: Wax applicator pad, clean rag, microfiber cloth, terry cloth

PERSONAL SAFETY:

Always use proper Personal Protective Equipment when using any TotalBoat product. Refer to the TotalBoat Premium Boat Wax Safety Data Sheet for more info.

SURFACE PREPARATION:

- Clean the surface thoroughly using TotalBoat Boat Soap. Remove any and all surface contamination including dust, dirt, grease, oils, water, or other waxes.
- For oxidized substrates, apply TotalBoat TotalBuff and TotalBoat TotalShine, as directed, prior to applying TotalBoat Premium Boat Wax.
- Ensure that the surface is completely dry before applying Premium Boat Wax.

APPLICATION:

- For best results, apply Premium Boat Wax only when conditions are between 50-90°F (0-90% relative humidity), and when rain, dew, or other precipitation will not affect the application process.
- Avoid applying product to hot surfaces or in direct sunlight, as the wax will dry too quickly for easy removal.
- Work in small 2' x 2' areas (or smaller) at a time.
- Apply a thin, even film of wax to the surface using a wax applicator pad, terry cloth, or other clean cloth suitable for the application.
- Do not apply a heavy coating of wax.
- Allow the film to dry to a haze (this may take roughly 30 seconds to two minutes) and remove using a clean microfiber cloth, or a suitable soft terry cloth.
- For optimal protection, wait 24-48 hours and apply a second coat of wax in the same fashion as the first one.
- Reapply Premium Boat Wax if water-beading properties or the shiny finish are no longer acceptable.

PRODUCT DATA:

Component:	Wax
Contains Abrasives:	Ultra-fine
Adds UV Protection:	Yes
Wax Content:	Carnauba
Application Method	Apply by hand using a rag, towel, microfiber cloth or terry cloth
Application Temperature/RH:	50-90°F, 0-90% RH
Substrates:	Fiberglass, gelcoat, epoxy, metals, paint, clear coat, automotive paints
Unit of Measure:	14 oz.
Cleanup:	Soap and water
Consistency:	Creamy paste
Density:	0.96 @ 20°C
Storage:	Store in a cool, dry area with the cap on tightly. Do not freeze.