



Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

1. Identification

Product identifier used on the label

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Recommended use of the chemical and restriction on use

Recommended use*: Raw material

Suitable for use in industrial sector: Chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

TOTALBOAT LLC

17 Peckham Drive

Bristol, RI 02809, USA

Telephone: +1 800 497-0010

Emergency telephone number

INFOTRAC: 1-800-535-5035

Other means of identification

Chemical family: Polymer, dispersion

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered. If the product adheres to skin, irritation may occur when it dries.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Canola Oil

CAS Number: 8002-13-9
Content (W/W): <1%
Synonym: No data available.

2-Methyl-4-Isothiazolin-3-one

CAS Number: 2682-20-4
Content (W/W): <.05%
Synonym: Kathon CG 243

mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

CAS Number: 55965-84-9
Content (W/W): <.05%
Synonym: 5-Chloro-2-methyl-3(2H)-isothiazolone mixt. with 2-methyl-3(2H)-isothiazolone

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. If irritation develops, seek medical attention.

If swallowed:

Immediately rinse mouth and then drink plenty of water, do not induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e., additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: Sodium bromide (NaBr)

Symptoms: Information, i.e., additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Information on: 2-Methyl-4-Isothiazolin-3-one

Symptoms: Overexposure may cause: corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Symptoms: Overexposure may cause: corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, foam, dry powder

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid contact with skin and eyes.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.
For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. No special measures necessary provided product is used correctly. Ensure adequate ventilation.

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Store protected against freezing.
Protect from temperatures below: 15°C
The packed product is destroyed at low temperatures or by frost.
Protect from temperatures above: 35°C
The packed product must be protected against exceeding the indicated temperature.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Canola Oil	OSHA PEL	TWA value 5 mg/m3 Respirable fraction; TWA value 15 mg/m3 Total dust;
------------	----------	---

Advice on system design:
Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate.

Hand protection:
Chemical resistant protective gloves

Eye protection:
Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

General safety and hygiene measures:
Hands and/or face should be washed before breaks and at the end of the shift. Avoid contact with skin and eyes.

9. Physical and Chemical Properties

Form:	Emulsion, low viscosity	
Odor:	faint odor	
Odor threshold:	No data available.	
Color:	off-white	
pH value:	9.0 - 10.0 (20°C)	
<i>Information on: Water</i>		
Melting point:	0°C	

<i>Information on: Water</i>		
Boiling point:	100°C	

Flash point:	> 300°F	(Unspecified)
Flammability:	not flammable	
Lower explosion limit:	not applicable	
Upper explosion limit:	not applicable	
Vapor pressure:	23 hPa (20°C)	
<i>Information on: Water</i>		
Vapor pressure:	23.4 hPa (20°C)	
	Literature data.	

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Density:	1.03 g/cm ³ @ 25°C
Relative density:	1.03 g/cm ³ @ 25°C
Vapor density:	not determined
Partitioning coefficient n-octanol/water (log Pow):	not applicable
Self-ignition temperature:	Not self-igniting
Solubility in water:	(15°C) partly soluble
Miscibility with water:	Miscible
Evaporation rate:	No data available.
Other Information:	Range of particle size: < 0,1 µm - 10 µm

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions. After long storage, slight quantities of carbon monoxide may be formed.

The product is chemically stable.

Conditions to avoid

Avoid extreme heat.

Incompatible materials

metal salts

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon dioxide, carbon monoxide, hydrocarbons

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. Ingestion may cause gastrointestinal disturbances. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Oral

Type of value: LD50
Species: rat
Value: > 2,000 - 10,000 mg/kg

Inhalation

Type of value: ATE
Value: > 5 mg/l
Exposure time: 4 h
Determined for mist

Dermal

Type of value: ATE
Value: > 5,000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Irritation / corrosion

Assessment of irritating effects: Not irritating to eyes and skin. May cause mechanical irritation. If the product adheres to skin, irritation may occur when it dries. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Skin

Species: rabbit
Result: non-irritant
Method: OECD Guideline 404

Eye

Species: rabbit
Result: non-irritant
Method: OECD Guideline 405

Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration Hazard

not applicable

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No adverse effects were observed after repeated exposure in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity: The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Assessment of reproduction toxicity: Not expected to cause reproductive toxicity (based on composition).

Teratogenicity

Assessment of teratogenicity: The data available for an assessment of the effect of the substance on developmental toxicity are not sufficient for a proper evaluation.

Experiences in humans

According to experience, the product is considered to be harmless to health if used in the correct manner.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The statement was derived from products of similar composition.

Symptoms of Exposure

No significant symptoms are expected due to the non-classification of the product.

12. Ecological Information

Toxicity

Toxicity to fish

LC50 (96 h) > 100 mg/l, Brachydanio rerio (OECD Guideline 203, static)

Aquatic invertebrates

EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

Aquatic plants

EC50 (72 h) > 100 mg/l, Scenedesmus subspicatus (OECD Guideline 201)
Nominal concentration.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

DIN EN ISO 8192-OECD 209-88/302/EEC, P. C activated sludge, domestic/EC20 (0.5 h): > 100 mg/l

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

The polymer component of the product is poorly biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

Elimination information

Not readily biodegradable.

Bioaccumulative potential

Bioaccumulation potential

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Mobility in soil

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

Assessment transport between environmental compartments

No data available.

Additional information

Adsorbable organically-bound halogen (AOX):

No data available.

Other ecotoxicological advice:

Do not release untreated into natural waters. At the present state of knowledge, no negative ecological effects are expected.

Ecological data are determined by analogy.

13. Disposal considerations

Waste disposal of substance:

Must be sent to a suitable incineration plant, observing local regulations.
Incinerate or dispose of in a licensed facility. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Safety Data Sheet

TOTALBOAT RAZZO ACRYLIC RESIN – PART A

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 1 Fire: 0 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

TOTALBOAT LLC

SDS Prepared on: 11/14/2022

Version: 1.0

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF SAFETY DATA SHEET