



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

1 Identification

- **Product identifier:**
- **Trade name:** TOTALBOAT WOOD SEALER
- **Product code:** TB-6580, TB-1227
- **Details of the distributor**
- **Distributor:**
TOTALBOAT LLC
17 Peckham Drive
BRISTOL, RI 02809
Phone: 800-497-0010
- **Emergency telephone number:** INFOTRAC: +1 (800) 535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226

Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340

May cause genetic defects.

Carcinogenicity 1B

H350

May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure 1

H372

Causes damage to the central nervous system through prolonged or repeated exposure.

Aspiration Hazard 1

H304

May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315

Causes skin irritation.

Sensitization - Skin 1

H317

May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3

H335-H336

May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Stoddard solvent

(Contd. on page 2)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 1)

Solvent Naphtha (Petroleum), Light Aromatic

1,2,4-Trimethylbenzene

Naphtha Solvent

2-butanone oxime

Decanedioic acid,bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation. May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 2)

· Dangerous components:		
64742-95-6	Solvent Naphtha (Petroleum), Light Aromatic	25-50%
8052-41-3	Stoddard solvent	25-50%
95-63-6	1,2,4-Trimethylbenzene	≤2.5%
25551-13-7	Trimethylbenzene	≤2.5%
96-29-7	2-butanone oxime	≥0.1-<1%
41556-26-7	Decanedioic acid,bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester	≥0.1-<1%
136-52-7	cobalt bis(2-ethylhexanoate)	≥0.1-≤2.5%
98-82-8	Cumene	≥0.1-≤2.5%
1330-20-7	Xylene	≥0.1-≤2.5%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If irritation occurs, get medical assistance.

- **After swallowing:** If symptoms persist consult doctor. Do not induce vomiting.

- **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 3)

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

8052-41-3	Stoddard solvent	300 mg/m ³
95-63-6	1,2,4-Trimethylbenzene	140 ppm
96-29-7	2-butanone oxime	30 ppm
108-67-8	1,3,5-trimethylbenzene (mesitylene)	140 ppm
108-83-8	2,6-dimethylheptan-4-one	75 ppm
98-82-8	Cumene	50 ppm
526-73-8	1,2,3-trimethylbenzene	140 ppm
1330-20-7	Xylene	130 ppm
111-76-2	2-butoxyethanol	60 ppm
25322-68-3	Polyethylene glycol	30 mg/m ³

· **PAC-2:**

8052-41-3	Stoddard solvent	1,800 mg/m ³
95-63-6	1,2,4-Trimethylbenzene	360 ppm
96-29-7	2-butanone oxime	56 ppm
108-67-8	1,3,5-trimethylbenzene (mesitylene)	360 ppm
108-83-8	2,6-dimethylheptan-4-one	330 ppm
98-82-8	Cumene	300 ppm
526-73-8	1,2,3-trimethylbenzene	360 ppm
1330-20-7	Xylene	920* ppm
111-76-2	2-butoxyethanol	120 ppm
25322-68-3	Polyethylene glycol	1,300 mg/m ³

· **PAC-3:**

8052-41-3	Stoddard solvent	29500** mg/m ³
95-63-6	1,2,4-Trimethylbenzene	480 ppm
96-29-7	2-butanone oxime	250 ppm
108-67-8	1,3,5-trimethylbenzene (mesitylene)	480 ppm
108-83-8	2,6-dimethylheptan-4-one	2000* ppm
98-82-8	Cumene	730 ppm
526-73-8	1,2,3-trimethylbenzene	480 ppm
1330-20-7	Xylene	2500* ppm
111-76-2	2-butoxyethanol	700 ppm
25322-68-3	Polyethylene glycol	7,700 mg/m ³

US

(Contd. on page 5)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

8052-41-3 Stoddard solvent	
PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 100 ppm
95-63-6 1,2,4-Trimethylbenzene	
REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: (25) NIC-10 ppm NIC-A4
96-29-7 2-butanone oxime	
WEEL	Long-term value: 10 ppm DSEN
136-52-7 cobalt bis(2-ethylhexanoate)	
TLV	Long-term value: 0.02* mg/m ³ as Co, A3; *inhalable; DSEN; RSEN; BEI
98-82-8 Cumene	
PEL	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL	Long-term value: 245 mg/m ³ , 50 ppm Skin

(Contd. on page 6)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 5)

TLV	Long-term value: 5 ppm A3
1330-20-7 Xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

· **Ingredients with biological limit values:**

1330-20-7 Xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 6)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Liquid
· Color:	Clear
· Odor:	Characteristic
· Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	166-177 °C (330.8-350.6 °F)

· Flash point: 40 °C (104 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 230 °C (446 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:	0.9 Vol %
· Upper:	6.2 Vol %

· Vapor pressure at 20 °C (68 °F): 2 hPa (1.5 mm Hg)

· Density at 20 °C (68 °F): 0.909 g/cm³ (7.58561 lbs/gal)

· Relative density: Not determined.

· Vapor density: Heavier than (Air)

· Evaporation rate: Slower than (n-Butyl Acetate)

· Solubility in / Miscibility with

· Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Dynamic: Not determined.

· Kinematic: Not determined.

· Solvent content:

· VOC content:	58.94 %
	535.8 g/l / 4.47 lb/gal

(Contd. on page 8)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 7)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent Naphtha (Petroleum), Light Aromatic

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

136-52-7	cobalt bis(2-ethylhexanoate)	2B
98-82-8	Cumene	2B
1330-20-7	Xylene	3
111-76-2	2-butoxyethanol	3

· **NTP (National Toxicology Program)**

98-82-8	Cumene	R
---------	--------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 8)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT	Paint
· IMDG, IATA	PAINT
· Transport hazard class(es)	
· DOT	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III

(Contd. on page 10)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 9)

· Environmental hazards:	Not applicable.
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	Flash Point – 100F or higher. D.O.T. label NOT required. 173.150(f)1 May be reclassified as Combustible Liquid.
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

8052-41-3	Stoddard solvent
95-63-6	1,2,4-Trimethylbenzene
96-29-7	2-butanone oxime
64742-47-8	Naphta Solvent
136-52-7	cobalt bis(2-ethylhexanoate)
98-82-8	Cumene
1330-20-7	Xylene
111-76-2	2-butoxyethanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Hazardous Air Pollutants

136-52-7	cobalt bis(2-ethylhexanoate)
98-82-8	Cumene
1330-20-7	Xylene

· Proposition 65

· Chemicals known to cause cancer:

98-82-8	Cumene
---------	--------

(Contd. on page 11)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 10)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

95-63-6	1,2,4-Trimethylbenzene	II
108-67-8	1,3,5-trimethylbenzene (mesitylene)	II
98-82-8	Cumene	D, CBD
526-73-8	1,2,3-trimethylbenzene	II
1330-20-7	Xylene	I
111-76-2	2-butoxyethanol	NL

· **TLV (Threshold Limit Value)**

1330-20-7	Xylene	A4
111-76-2	2-butoxyethanol	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Stoddard solvent
Solvent Naphtha (Petroleum), Light Aromatic
1,2,4-Trimethylbenzene
Naphtha Solvent
2-butanone oxime
Decanedioic acid,bis(1,2,2,6,6-pentamethyl-4-piperidiny) ester

· **Hazard statements**

Flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May cause respiratory irritation. May cause drowsiness or dizziness.
Causes damage to the central nervous system through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 12)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 11)

Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
 Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 09/30/2022 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health

(Contd. on page 13)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/30/2022

Reviewed on 09/30/2022

Trade name: TOTALBOAT WOOD SEALER

(Contd. of page 12)

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Sensitization - Skin 1: Skin sensitisation – Category 1

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1B: Carcinogenicity – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1

Aspiration Hazard 1: Aspiration hazard – Category 1

US