

TotalBoat Podium Finish -- Tech Data Sheet

SUPPORT PRODUCTS:

Products Commonly Used with Podium Finish: TotalBoat TotalBuff, TotalBoat TotalShine, TotalBoat Boat Soap

APPLICATION:

SUBSTRATES: For use on fiberglass, gelcoat, and paint. Test any painted surfaces in a small, inconspicuous spot before full application.

GENERAL APPLICATION:

1 Wash surface to be polished thoroughly with TotalBoat Boat Soap to remove any surface contaminants.

2 If fiberglass is chalky or faded, compound with TotalBoat TotalBuff then use TotalShine to restore the surface color and shine before applying.

3 Apply TotalBoat Podium Finish with a clean cloth or lint-free rag using a circular motion. Allow to dry to a haze. This should only take a few minutes.

4 Wipe the surface in a circular motion with a clean cloth to wipe off extra material and polish to a shiny surface. No hard rubbing is necessary. Two applications are recommended for best results and protection.

5 If desired, a maintenance coat of TotalBoat Podium Finish every 2-3 months will help maintain superior protection, shine, and drag reduction. It is recommended that dry sailed or regularly hauled boats using Podium Finish below the water should reapply every 2-3 weeks for optimal performance.

Note: Podium Finish is not designed as an antifouling coating, but it may reduce staining and growth at or below the waterline.

APPLICATION DATA:

Application Method: Rag, terrycloth towel, microfiber cloth

Substrates: Fiberglass, metal, glass, painted surfaces (always test before performing full application)

Number of Coats: At least 2 (for best results)

Pot Life: N/A

Coverage (sq ft/gal): N/A

Application Temp/RH: 50-100°F, 0-90%

PHYSICAL DATA:

Color: White, becomes clear when polished onto surface

Components: One

Finish: Gloss

Storage: Cool, dry area

Flash Point: N/A

Units: Pint (16 oz.)

Solids (% by Volume): N/A

VOC (lb/gal): N/A