

TotalBoat Eco Solvent -- Tech Data Sheet

APPLICATIONS:

- * Cleaning rollers, tools, composite lamination tools, molds, and spray guns
- * Environmentally friendly cleanup for paints, polyester resins, epoxy resins, vinyl ester resins, contact cement, varnishes, and enamels
- * Surface prep solvent for composites, bonding, and painting surfaces
- * Removes uncured resins/paints from a number of substrates

ADVANTAGES OVER OTHER SOLVENTS

- * Evaporates completely, leaving no residue at all.
- * Removes paint, ink, varnishes, uncured resin, epoxies, decals, tree sap, grease, gum residue, and Sharpie® marks.
- * Evaporation rate is 5-10 times that of traditional petroleum-based solvents.
- * TotalBoat Eco Solvent is reusable; it can be recycled using affordable polypropylene filters.
- * 100% bio-based, environmentally friendly, contains no water.
- * Reduces health hazards.

APPLICATION DATA:

Uses: Solvent wipe, tool cleanup
Type of Solvent: Surface Prep, Cleanup
Safe Substrates for Use: Aluminum, Stainless Steel, Carbon Steel, Latex, Nylon, Polyethylene, Polypropylene, PTFE, Teflon®, Fiberglass
Pot Life: N/A
Coverage (sq ft/gal): Depends on application

PHYSICAL DATA:

Color: Clear
Components: One
Storage: Store in a cool, well-ventilated area away from all sources of ignition and out of direct sunlight. Store in a dry location away from heat. Keep away from incompatible materials. Keep containers closed tightly.
Specific Gravity: 0.988
Flash Point/Boiling Point: 133°F/200°F
Solids (% by Volume): 0%
Units: Pint, Quart, Gallon
VOC Content: < 990g/L

